
ADVANCED HIGH CEILING


## SH-130 - Solar LED Paver

## Water Proof / No Wiring





METEOR Solar LED Paver lights incorporate state-of-the-art technology, combining the best solar panels, power storage and optical design to create products that will function for years to come.



Quantity

**Project** 

Note

**Type** 

General

Weight: 0.968 lbs

Rim Finish: Brushed/Polished stainless steel; Optional: SUS316

stainless steel / Brass

Lens: GE super light permeable PC

Housing: SUS304 stainless steel, cast aluminum

Power Storage: Ultracapacitor

Operational

Operation Time: Minimum 12 hours(fully charged) 4-8 hours(overcast)

Full Charge Time: 6 hours(direct sunlight)
Switch: Light sensitive auto on/off

**Environmental** 

Compressive Strength: 9902 lbs/4456 kgs(maximum)

Operating Temperature: -4° F to 140° F Storage Temperature: -13° F to 176° F

Warranty

3 year limited warranty. See <a href="www.meteor-lighting.com">www.meteor-lighting.com</a> for details.











## How To Specify Ordering Example: SH130C-AMB-BS-HS

Model			ССТ		Finish		Housing	
SH130C	(Product)	АМВ	(Amber)	BS	(Brushed Stainless Steel)	HS	(Housing and Anchor Plate Included)	
SH130B	(Battery sample)	BLU	(Blue)	PS	(Polished Stainless Steel)			
	. ,	GEN	(Green)	SS	(SUS316 Stainless Steel)			
		RED	(Red)	BR	(Brass)			
		WHT	(White/5500-6000K)					
		WAM	(Warm White/2800-3000K)					

\*Color LUX(Average)
White 30
Amber 25
Red 70
Blue 25
Green 60
Warm White 28